

Safety Data Sheet

Leishman's Stain

Section 1 - Chemical Product and Company Identification

SDS Name: Leishman's Stain

Catalog Numbers: SO-575, B-157-1

Company Identification: Transene Company, Inc., DBA ROWLEY BIOCHEMICAL Inc.
10 ELECTRONICS AVENUE
DANVERS, MA 01923

For information, call: 978-739-4883

Emergency Number: 800-424-9300

For CHEMTREC assistance, call: 800-424-9300

Section 2 - Hazards Identification

GHS Classifications

H225-Flammable liquids: 2

H301-Acute toxicity, oral: 3

H311-Acute toxicity, dermal: 3

H319-Serious eye damage/eye irritation: 2A

H331-Acute toxicity, inhalation: 3

H361-Reproductive toxicity: 2

H370-Specific target organ toxicity, single exposure: 1

H372-Specific target organ toxicity, repeated exposure: 1

Pictograms or Hazard Symbols and Hazard Statement(s):



Signal Word: Danger

Hazard Statements:

H225-Highly flammable liquid and vapour

H301-Toxic if swallowed

H311-Toxic in contact with skin

H319-Causes serious eye irritation

H331-Toxic if inhaled
H361-Suspected of damaging fertility or the unborn child
H370-Causes damage to organs (target organs: optic nerve)
H372-Causes damage to organs through prolonged or repeated exposure (target organs: kidney, liver, spleen, and blood)

Precautionary Statements:

P201-Obtain special instructions before use.
P202-Do not handle until all safety precautions have been read and understood.
P210-Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P233-Keep container tightly closed.
P240-Ground and bond container and receiving equipment.
P241-Use explosion-proof electrical/ventilating/lighting/equipment.
P242-Use non-sparking tools.
P243-Take action to prevent static discharges.
P260-Do not breathe dust/fume/gas/mist/vapours/spray.
P261-Avoid breathing dust/fume/gas/mist/vapours/spray.
P264-Wash thoroughly after handling.
P270-Do not eat, drink, or smoke when using this product.
P271-Use only outdoors or in a well-ventilated area.
P280-Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310-If swallowed: Immediately call a Poison Center/doctor.
P302+P352-If on skin: Wash with plenty of soap and water.
P303+P361+P353-If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340-If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338-If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P311-If exposed or concerned: Call a Poison Center/doctor.
P308+P313-If exposed or concerned: Get medical advice/attention.
P311-Call a Poison Center or doctor.
P312-Call a Poison Center/doctor if you feel unwell.
P314-Get medical advice/attention if you feel unwell.
P330-Rinse mouth.
P337+P313-If eye irritation persists: Get medical advice/attention.
P361+P364-Take off immediately all contaminated clothing and wash it before reuse.
P370+P378-In case of fire: Use dry chemical, carbon dioxide, dry sand, water spray, or alcohol-resistant foam to extinguish.
P403+P233-Store in a well-ventilated place. Keep container tightly closed.
P403+P235-Store in a well-ventilated place. Keep cool.
P405-Store locked up.
P501-Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent
12627-53-1	Leishman's Stain	0.2 w/v
67-56-1	Methyl Alcohol	balance

Section 4 - First Aid Measures

Eye Exposure: In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

Dermal Exposure: In case of skin contact, flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing and shoes. Get immediate medical attention. Wash clothing/shoes before reuse.

Oral Exposure: If swallowed, seek immediate medical advice. Do not induce vomiting unless directed by a physician.

Inhalation Exposure: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Immediate medical attention is required.

Section 5 - Fire Fighting Measures

General Information: Flammable liquid and vapor. Risk of ignition. Containers can build up pressure if exposed to heat and/or fire. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Vapors can travel to a source of ignition and flash back. Will burn if involved in a fire. Can release vapors that form explosive mixtures at temperatures above the flashpoint. Use water spray to keep fire-exposed containers cool. Containers may explode in the heat of a fire.

Extinguishing Media: For small fires use alcohol-resistant foam, dry chemical, or carbon dioxide. For large fires use water spray, fog, or alcohol-resistant foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do NOT use straight streams of water. Do NOT use water jet.

Hazardous Combustion Products: Carbon oxides, nitrogen oxides, formaldehyde, hydrogen bromide, irritating and toxic fumes and gases.

Flash Point: Not available

Autoignition Temperature: Not available

Explosion Limits, Lower: Not available

Upper: Not available

NFPA Rating: (estimated) Health: 1; Flammability: 3; Instability: 0

Note: Keep away from heat, sparks, or flames. Take precautionary measures against static discharges.

Section 6 - Accidental Release Measures

Procedure(s) of Personal Precaution(s):

Wear personal protective equipment and NIOSH approved respirator. Do not ingest or inhale. Do not get on skin or clothing. Do not get in eyes. Ensure adequate ventilation.

Keep away from heat. Eliminate all sources of ignition. Take precautionary measures against static discharges.

Methods for Cleaning up: Absorb with sand, earth, or vermiculite. Carefully sweep up and containerize for proper disposal. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Ground metal parts of equipment. Do not release to the environment. Do not release to drains.

Section 7 - Handling and Storage

Use care when handling. Wear personal protective equipment. Wash thoroughly after handling. Use with adequate ventilation. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Do not ingest. Use under a chemical fume hood. Store in a tightly closed container in a cool, dry, and well-ventilated place. Keep away from incompatible materials. Protect from heat. Vapors heavier than air, may travel considerable distance and ignite or explode. Keep away from direct sunlight, open flames, hot surfaces, and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls: Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Respirators: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

Exposure Limits:

Chemical Name	ACGIH - TLV	NIOSH - IDLH	OSHA - Final PELs
Leishman's Stain CAS#12627-53-1	Not listed	Not listed	Not listed
Methyl Alcohol CAS#67-56-1	200 ppm TWA 250 ppm STEL	200 ppm TWA 260 mg/m ³ TWA 250 ppm STEL 325 mg/m ³ STEL 6000 ppm IDLH	200 ppm TWA 260 mg/m ³ TWA 250 ppm STEL 325 mg/m ³ STEL

OSHA Vacated PELs: Methyl Alcohol: 200 ppm TWA; 260 mg/m³ TWA; 250 ppm STEL; 325 mg/m³ STEL

Section 9 - Physical and Chemical Properties

Physical State: Liquid
Appearance: Dark blue
Odor: Alcohol-like
Vapor Pressure: Not available
Odor Threshold: Not available
Vapor Density: Not available
pH: Not available
Relative Density: Not available
Melting point/freezing point: Not available
Solubility: Not available
Boiling Point: Not available
Flash Point: Not available
Evaporation Rate: Not available
Flammability (solid, gas): Not available
Partition coefficient: n-octanol/water: Not available
Auto-ignition Temperature: Not available
Decomposition Temperature: Not available
Viscosity: Not available
Specific Gravity/Density: Not available

Section 10 - Stability and Reactivity

Chemical Stability: Stable under normal temperatures and pressures. Note: Vapors may form explosive mixtures with air.

Conditions to Avoid: Incompatible materials, ignition sources, excess heat, hot surfaces, and oxidizers. Protect from sunlight.

Incompatibilities with Other Materials: Oxidizing agents, acids, alkali metals, reducing agents, acid anhydrides, acid chlorides, peroxides, ammonia, hydrazine, peroxides, sodium, acid anhydrides, calcium hypochlorite, chromyl chloride, nitrosyl perchlorate, bromine pentafluoride, perchloric acid, silver nitrate, mercuric nitrate, potassium-tert-butoxide, magnesium perchlorate, acid chlorides, platinum, uranium hexafluoride, silver oxide, iodine heptafluoride, acetyl bromide, disulfuryl difluoride, tetrachlorosilane + water, acetyl chloride, permanganic acid, ruthenium (VIII) oxide, uranyl perchlorate, and potassium dioxide.

Hazardous Decomposition Products: Carbon oxides, nitrogen oxides, hydrogen bromide, formaldehyde, irritating and toxic fumes and gases.

Section 11 - Toxicological Information

CAS#12627-53-1 Leishman's Stain:

LD50 Oral: Not available

LD50 Dermal: Not available

LC50 Inhalation: Not available

Carcinogenicity: Leishman's Stain CAS#12627-53-1 is not listed by IARC, NTP, ACGIH, OSHA, or California Prop 65.

CAS#67-56-1 Methyl Alcohol: RTECS#: PC1400000

LD50 Oral: >1187-2769 mg/kg (rat)

LD50 Dermal: 17100 mg/kg (rabbit)

LC50 Inhalation: 128.2 mg/L (rat) 4h

Carcinogenicity: Methyl Alcohol CAS# 67-56-1 is not listed by IARC, NTP, ACGIH, or OSHA. Methyl Alcohol is listed by California Prop. 65 as a developmental carcinogen.

Information on the likely routes of exposure: Routes of entry anticipated: oral, dermal, inhalation, and eye.

Epidemiology: Not available.

Teratogenicity: Not available.

Reproductive Effects: May damage fertility or the unborn child.

Developmental Effects: Not available.

Neurotoxicity: Not available.

Mutagenicity: Not available.

Specific Target Organ Toxicity, Single Exposure: Optic nerve.

Specific Target Organ Toxicity, Repeated Exposure: Kidney, liver, spleen, and blood.

Other Studies: May affect behavior/central nervous system, urinary system, kidneys (renal failure), cardiovascular system, and liver.

Symptoms associated with exposure: Toxic if inhaled. Toxic if swallowed. Toxic in contact with skin.

Inhalation note: Toxic. An irritant to the mucous membranes. Toxic effects exerted upon nervous system, particularly the optic nerve. Once absorbed into the body, it is very slowly eliminated. Symptoms of overexposure may include headache, drowsiness, nausea, vomiting, blurred vision, blindness, coma, and death. A person may get better but then worse again up to 30 hours later.

Ingestion note: Toxic. Symptoms parallel inhalation. Can intoxicate and cause blindness. Usual fatal dose = 100-125 mL.

Skin contact note: Toxic. Methyl alcohol is a defatting agent and may cause skin to become dry and cracked. Skin absorption can occur. Symptoms parallel inhalation exposure.

Eye contact note: Serious eye irritant. Continued exposure may cause eye lesions.

The toxicological properties of this material have not been thoroughly investigated.

Section 12 - Ecological Information

Ecotoxicity: Do not release to the environment. Do not release to drains. Harmful to aquatic life.

CAS#67-56-1 Methyl Alcohol:

LC50, freshwater fish: >10000 mg/L 96h (pimephales promelas)(fathead minnow)

EC50, water flea: >10000 mg/L 24h

EC50, algae: 22000 mg/L 96h (pseudokirchneriella subcapitata)(green algae)

IC50, bacteria: >1000 mg/L 3h (activated sludge)

Persistence and degradability: Not available.

Bio-accumulative potential: Not available.

Mobility: The material will likely be mobile in the environment due to its volatility.

Section 13 - Disposal Considerations

DISPOSAL: Dispose of in accordance with all federal, state, and local regulations.

Section 14 – Transport Information

DOT

Proper shipping name: Methanol

UN1230

PG II

Hazard class 3 (flammable)

Section 15 - Regulatory Information

Canada Regulatory Information

WHMIS Classification: This product has been classified in accordance with the hazard criteria of the CPR, and the SDS contains all the information required by the CPR.

Section 16 - Additional Information

SDS Creation Date: 8-14-19

Revision #1. 12-15-22

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users

should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Rowley Biochemical, Inc. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages, howsoever arising, even if Rowley Biochemical, Inc. has been advised of the possibility of such damages.