

Safety Data Sheet

Eosin Y-Phloxine B Solution

Section 1 - Chemical Product and Company Identification

SDS Name: Eosin Y-Phloxine B Solution

Catalog Numbers: SO-630, L-763-3

Company Identification: Transene Company, Inc., DBA ROWLEY BIOCHEMICAL, Inc.
10 ELECTRONICS AVENUE
DANVERS, MA 01923

For information, call: 978-739-4883

Emergency Number: 800-424-9300

For CHEMTREC assistance, call: 800-424-9300

Section 2 - Hazards Identification

GHS Classifications

H225-Flammable liquids: 2

H303-Acute toxicity, oral: 5

H317-Sensitisation, skin: 1

H319-Serious eye damage/eye irritation: 2A

H370-Specific target organ toxicity, single exposure: 1

H372-Specific target organ toxicity, repeated exposure: 1

Pictograms or Hazard symbols and Hazard statement(s):



Signal Word: Danger

Hazard Statements:

H225-Highly flammable liquid and vapour

H303-May be harmful if swallowed

H317-May cause an allergic skin reaction

H319-Causes serious eye irritation

H370-Causes damage to organs (target organs: respiratory system, central nervous system, and optic nerve)

H372-Causes damage to organs through prolonged or repeated exposure (target organs: kidney, liver, spleen, and blood)

Precautionary Statements:

P210-Keep away from heat, flames, sparks, open flames, and other ignition sources. No smoking.

P233-Keep container tightly closed.

P240-Ground and bond container and receiving equipment.

P241-Use explosion-proof electrical/ventilating/lighting equipment.

P242-Use non-sparking tools.

P243-Take action to prevent static discharges.

P260-Do not breathe dust/fume/gas/mist/vapours/spray.

P261-Avoid breathing dust/fume/gas/mist/vapours/spray.

P264-Wash thoroughly after handling.

P270-Do not eat, drink, or smoke when using this product.

P272-Contaminated work clothing should not be allowed out of the workplace.

P280-Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312-If swallowed: Call a Poison Center/doctor if you feel unwell.

P302+P352-If on skin: Wash with plenty of soap and water.

P303+P361+P353-If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338-If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311-If exposed or concerned: Call a Poison Center/doctor.

P314-Get medical advice/attention if you feel unwell.

P333+P313-If skin irritation or rash occurs: Get medical advice/attention.

P337+P313-If eye irritation persists: Get medical advice/attention.

P362+P364-Take off contaminated clothing and wash it before reuse.

P370+P378-In case of fire: Use dry chemical, carbon dioxide, dry sand, water spray or alcohol-resistant foam to extinguish.

P403+P235-Store in a well-ventilated place. Keep cool.

P405-Store locked up.

P501-Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent
17372-87-1	Eosin Y	0.1 w/v
18472-87-2	Phloxine B	0.01 w/v
64-17-5	Ethyl Alcohol	79 v/v
67-56-1	Methyl Alcohol	4.1 v/v
64-19-7	Glacial Acetic Acid	0.45 v/v
7732-18-5	Water	Balance

Section 4 - First Aid Measures

Eye Exposure: In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Get medical attention.

Dermal Exposure: In case of skin contact, flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention.

Oral Exposure: If swallowed, get immediate medical advice. Rinse mouth with water.

Inhalation Exposure: If inhaled, remove to fresh air. If breathing becomes difficult, call a physician.

Section 5 - Fire Fighting Measures

General Information: Containers can build up pressure if exposed to heat and/or fire. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Vapors can travel to a source of ignition and flash back. Will burn if involved in a fire. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures above the flashpoint. Use water spray to keep fire-exposed containers cool. Containers may explode in the heat of a fire.

Extinguishing Media: For small fires, use dry chemical, carbon dioxide, dry sand, water spray or alcohol-resistant foam. For large fires, use water spray, fog, or alcohol-resistant foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do NOT use straight streams of water.

Hazardous Combustion Products: Carbon oxides, sodium oxides, hydrogen chloride gas, chlorine, formaldehyde, hydrogen bromide gas, bromine, irritating and toxic fumes and gases.

Flash Point: Not available

Autoignition Temperature: Not available

Explosion Limits, Lower: Not available

Upper: Not available

NFPA Rating: (estimated) Health: 2; Flammability: 4; Instability: 0

NOTE: Static discharge could act as an ignition source.

Section 6 - Accidental Release Measures

Procedure(s) of Personal Precaution(s):

Wear personal protective equipment. Do not ingest or inhale. Do not get on skin or clothing. Do not get in eyes. Ensure adequate ventilation. Keep away from heat. Eliminate all sources of ignition.

Methods for Cleaning up: Absorb with inert material such as sand, earth, or vermiculite. Do NOT absorb with combustible material such as saw dust or cellulosic material. Carefully sweep up and containerize for proper disposal. Use only non-sparking tools. Use explosion-proof equipment and take precautionary measures against static discharge. Do not release to the environment. Do not release to drains.

Section 7 - Handling and Storage

Use care when handling. Wear personal protective equipment. Wash thoroughly after handling. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation. Keep in a tightly closed and non-metal container. Store in a cool, dry, and well-ventilated place. Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting equipment. Use proper grounding procedures to avoid static electricity. Keep away from incompatible materials. Protect from heat. Protect from moisture. Vapors heavier than air may travel considerable distance and ignite or explode.

Note: Static discharge could act as an ignition source.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls: Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Respirators: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

Exposure Limits:

Chemical Name	ACGIH - TLV	NIOSH - IDLH	OSHA - Final PELs
Eosin Y CAS#17372-87-1	Not listed	Not listed	Not listed
Phloxine B CAS#18472-87-2	Not listed	Not listed	Not listed
Ethyl Alcohol CAS#64-17-5	1000 ppm STEL	1000 ppm TWA 1900 mg/m ³ TWA 3300 ppm IDLH	1000 ppm TWA 1900 mg/m ³ TWA
Methyl Alcohol CAS#67-56-1	200 ppm TWA 250 ppm Skin STEL	200 ppm TWA 260 mg/m ³ TWA 250 ppm STEL 325 mg/m ³ STEL 6000 ppm IDLH	200 ppm TWA 260 mg/m ³ TWA
Glacial Acetic Acid CAS#64-19-7	10 ppm TWA 15 ppm STEL	10 ppm TWA 25 mg/m ³ TWA 15 ppm STEL 37 mg/m ³ STEL 50 ppm IDLH	10 ppm TWA 25 mg/m ³ TWA

OSHA Vacated PELs: Ethyl Alcohol: 1000 ppm TWA; 1900 mg/m³ TWA
Methyl Alcohol: 200 ppm TWA; 260 mg/m³ TWA; 250 ppm STEL;
325 mg/m³ Skin STEL
Glacial Acetic Acid: 10 ppm TWA; 25 mg/m³ TWA

Section 9 - Physical and Chemical Properties

Physical State: Liquid
Appearance: Pink-red
Odor: Alcohol-like
Vapor Pressure: Not available
Odor Threshold: Not available
Vapor Density: Not available
pH: Not available
Relative Density: Not available
Melting point/freezing point: Not available
Solubility: Soluble in water
Boiling Point: Not available
Flash Point: Not available
Evaporation Rate: Not available
Flammability (solid, gas): Not available
Partition coefficient: n-octanol/water: Not available
Autoignition Temperature: Not available
Decomposition Temperature: Not available
Viscosity: Not available
Specific Gravity/Density: Not available

Section 10 - Stability and Reactivity

Chemical Stability: Stable under normal temperatures and pressures. Reacts violently with oxidizers: Risk of fire/explosion.

Conditions to Avoid: Avoid direct sunlight and extremely high or low temperatures. Avoid all possible sources of ignition (spark or flame). Keep away from hot surfaces and avoid incompatible materials. Exposure to moisture.

Incompatibilities with Other Materials: Strong oxidizing agents, acids, reducing agents, strong bases, metals, chromic acid, ethylene glycol, nitric acid, phosphorous trichloride, oxidizers, sodium peroxide, strong caustics, carbonates, hydroxides, oxides, phosphates, alkaline, alkali metals, ammonia, hydrazine, peroxides, sodium, acid anhydrides, calcium hypochlorite, chromyl chloride, nitrosyl perchlorate, bromine pentafluoride, perchloric acid, silver nitrate, mercuric nitrate, potassium-tert-butoxide, magnesium perchlorate, acid chlorides, platinum, uranium hexafluoride, silver oxide, iodine heptafluoride, acetyl bromide, disulfuryl difluoride, tetrachlorosilane + water, acetyl chloride, permanganic acid, ruthenium (VIII) oxide, uranyl perchlorate, and potassium dioxide.

Hazardous Decomposition Products: Carbon oxides, sodium oxides, hydrogen chloride gas, chlorine, formaldehyde, hydrogen bromide gas, bromine, irritating and toxic fumes and gases.

Section 11 - Toxicological Information

CAS#17372-87-1 Eosin Y: RTECS#: LM580000

LD50 Oral: 2344 mg/kg (mouse)
LD50 Dermal: >2000 mg/kg (rat)
LC50 Inhalation: Not available

Carcinogenicity: Eosin Y CAS#17372-87-1 is not listed by IARC, NTP, ACGIH, OSHA, or California Prop. 65.

CAS#18472-87-2 Phloxine B: RTECS#: LM590000

LD50 Oral: 8400 mg/kg (rat)
LD50 Dermal: >2000 mg/kg (rat)
LC50 Inhalation: Not available

Carcinogenicity: Phloxine B CAS#18472-87-2 is not listed by IARC, NTP, ACGIH, OSHA, or California Prop. 65.

Tumorigenic Effects: Liver, and endocrine.

Reproductive Effects: Craniofacial, musculoskeletal system, and fetotoxicity. Tests on laboratory animals for reproductive effects are cited in RTECS.

Mutagenic Effects: Mutation in mammalian somatic cells (human, lungs). Tests on laboratory animals for mutagenic effects are cited in RTECS.

CAS#64-17-5 Ethyl Alcohol: RTECS#: KQ630000

LD50 Oral: 10470 mg/kg (rat)
LD50 Dermal: Not available
LC50 Inhalation: 124.7 mg/L 4h (rat)

Tumorigen, mutagen, reproductive effector per RTECS.

Draize test, rabbit, eye: 500 mg/24h Mild Irritant.

Skin: Repeated exposure may cause skin dryness or cracking.

Ethyl Alcohol overexposure may lead to headache, dizziness, tiredness, nausea, and vomiting.

Carcinogenicity: Ethyl Alcohol CAS#64-17-5 is not listed by OSHA. Ethyl Alcohol is listed by IARC (Group 1, Carcinogenic to Humans), NTP (Known Carcinogen), and ACGIH (A3, Animal Carcinogen). Ethyl Alcohol is listed by California Prop. 65 as a developmental carcinogen (alcoholic beverages only).

CAS#67-56-1 Methyl Alcohol: RTECS#: PC140000

LD50 Oral: 100.1 mg/kg (expert judgement)
LD50 Dermal: 300.1 mg/kg (expert judgement)
LC50 Inhalation: 3.1 mg/L 4h vapor (expert judgement)

Mutagen, reproductive effector per RTECS.

Draize test, rabbit, eye: 100 mg/24h Moderate Irritant.

Draize test, rabbit, skin: 20 mg/24h Moderate Irritant.

Carcinogenicity: Methyl Alcohol CAS#67-56-1 is not listed by IARC, NTP, ACGIH, or OSHA. Methyl Alcohol is listed by California Prop. 65 as a developmental carcinogen.

CAS#64-19-7 Glacial Acetic Acid: RTECS#: AF122500

LD50 Oral: 3310 mg/kg (rat)

LD50 Dermal: 1060 mg/kg (rabbit)

LC50 Inhalation: 11.4 mg/L 4h (rat)

Mutagen, reproductive effector per RTECS.

Skin corrosion/irritation: skin (rabbit), causes severe burns.

Serious eye damage/eye irritation: eyes (rabbit), corrosive to eyes, and causes serious eye damage.

Carcinogenicity: Glacial Acetic Acid CAS#64-19-7 is not listed by IARC, NTP, ACGIH, OSHA, or California Prop. 65.

Information on the likely routes of exposure: Routes of entry anticipated: oral, dermal, inhalation, and eye.

Epidemiology: Not available.

Teratogenicity: Not available.

Reproductive Effects: Phloxine B (CAS#18472-87-2): Craniofacial, musculoskeletal system, and fetotoxicity. Tests on laboratory animals for reproductive effects are cited in RTECS.

Developmental Effects: Not available

Neurotoxicity: Not available.

Mutagenicity: Phloxine B (CAS#18472-87-2): Mutation in mammalian somatic cells (human, lungs). Tests on laboratory animals for mutagenic effects are cited in RTECS.

Tumorigenic Effects: Phloxine B (CAS#18472-87-2): Liver, and endocrine.

Specific Organ Toxicity, Single Exposure: Respiratory system, central nervous system, and optic nerve.

Specific Organ Toxicity, Repeated Exposure: Kidney, liver, spleen, and blood.

Symptoms associated with exposure: Prolonged or repeated exposure can defat the skin and lead to irritation, cracking, and/or dermatitis. May cause an allergic skin reaction. Eye contact may result in corneal damage, blindness, pain, irritation, watering, redness, blurred or double vision. Causes damage to organs if in contact with skin, if inhaled or if swallowed. Overexposure may lead to headache, dizziness, tiredness, nausea, vomiting. Experimental mutagen, teratogen, tumorigen (Phloxine B CAS#18472-87-2).

The toxicological properties of this material have not been thoroughly investigated.

Section 12 - Ecological Information

Ecotoxicity: Do not release to the environment. Do not release to drains. Toxic to aquatic life. May cause long-term adverse effects to the environment.

CAS#17372-87-1 Eosin Y:

LC50, freshwater fish: 1200 mg/L 48h (oryzias latipes)(orange-red killifish)

EC50, water flea: >100 mg/L 48h static (daphnia magna)
ErC50, algae: 51.3 mg/L 72h static (desmodesmus subspicatus)(green algae)

CAS#18472-87-2 Phloxine B:

LC50, freshwater fish: 97.7 mg/L 96h (gambusia affinis)(mosquito fish)

CAS#64-17-5 Ethyl Alcohol:

LC50, freshwater fish: 14200 mg/L 96h (pimephales promelas)(fathead minnow)

EC50, freshwater algae: 275 mg/L 72h (chlorella vulgaris)

EC50, water flea: 9268 mg/L 48h

EC50, water flea: 10800 mg/L 24h

IC50, bacteria: >1000 mg/L 3h (activated sludge)

EC50, microtox: 34634 mg/L 30min (photobacterium phosphoreum)

EC50, microtox: 35470 mg/L 5min (photobacterium phosphoreum)

CAS#67-56-1 Methyl Alcohol:

LC50, freshwater fish: 15400 mg/L 96h flow-through (lepomis macrochirus)(bluegill)

LC50, freshwater fish: 19000 mg/L 96h (oncorhynchus mykiss)(rainbow trout)

EC50, water flea: 18260 mg/L 96h semi-static (daphnia magna)

ErC50, algae: 22000 mg/L 96h static (pseudokirchneriella subcapitata)(green algae)

IC50, bacteria: >1000 mg/L 3h static (activated sludge)

CAS#64-19-7 Glacial Acetic Acid:

LC50, freshwater fish: 88 mg/L 96h (pimephales promelas)(fathead minnow)

LC50, freshwater fish: 75 mg/L 96h (lepomis macrochirus)(bluegill)

EC50, water flea: 95 mg/L 24h

EC50, microtox: 8.8 mg/L 5min

Persistence and degradability: Not available.

Bio-accumulative potential: Not available.

Mobility: Will likely be mobile in the environment due to its water solubility and volatility.

Section 13 - Disposal Considerations

DISPOSAL: Dispose of in accordance with all federal, state, and local regulations.

Section 14 - Transport Information

DOT

Proper shipping name: Alcohols, N.O.S.

UN1987

PG II

Hazard class 3 (flammable)

Section 15 - Regulatory Information

Canada Regulatory Information

WHMIS Classification: This product has been classified in accordance with the hazard criteria of the CPR, and the SDS contains all the information required by the CPR.

Section 16 - Additional Information

SDS Creation Date: 2/2/12

Revision #1: 4/3/13 RC

Revision #2: 3/28/17

Revision #3: 10-19-21

Revision #4: 11-10-23

Revision #5: 1-5-26

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Rowley Biochemical, Inc. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages, howsoever arising, even if Rowley Biochemical, Inc. has been advised of the possibility of such damages.