# Safety Data Sheet Gum Mastic, 10% in Isopropanol

Section 1 - Chemical Product and Company Identification

 SDS Name: Gum Mastic, 10% in Isopropanol
 Catalog Numbers: SO-567
 Company Identification: Transene Company, Inc., DBA ROWLEY BIOCHEMICAL, Inc. 10 ELECTRONICS AVENUE DANVERS, MA 01923
 For information, call: 978-739-4883
 Emergency Number: 800-424-9300
 For CHEMTREC assistance, call: 800-424-9300

Section 2 - Hazards Identification

# **GHS Classifications**

H225-Flammable liquids: 2 H303-Acute toxicity, oral: 5 H319-Serious eye damage/eye irritation: 2A H336-Specific target organ toxicity, single exposure; Narcotic effects: 3 H373-Specific target organ toxicity, repeated exposure: 2

10% of the mixture consists of ingredients of unknown acute oral toxicity.10% of the mixture consists of ingredients of unknown acute inhalation toxicity.

# **Pictograms or Hazard symbols and Hazard Statement(s):**



Signal Word: Danger

# **Hazard Statements:**

H225-Highly flammable liquid and vapour H303-May be harmful if swallowed H319-Causes serious eye irritation H336-May cause drowsiness or dizziness H373-May cause damage to organs through prolonged or repeated exposure (target organs: kidney and liver)

# **Precautionary Statements:**

P210-Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

P233-Keep container tightly closed.

P240-Ground and bond container and receiving equipment.

P241-Use explosion-proof electrical/ventilating/lighting equipment.

P242-Use non-sparking tools.

P243-Take action to prevent static discharges.

P260-Do not breathe dust/fume/gas/mist/vapours/spray.

P261-Avoid breathing dust/fume/gas/mist/vapours/spray.

P264-Wash thoroughly after handling.

P271-Use only outdoors or in a well-ventilated area.

P280-Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312-If swallowed: Call a Poison Center/doctor if you feel unwell.

P303+P361+P353-If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340-If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338-If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312-Call a Poison Center/doctor if you feel unwell.

P314-Get medical advice/attention if you feel unwell.

P337+P313-If eye irritation persists: Get medical advice/attention.

P370+P378-In case of fire: Use dry chemical, carbon dioxide, dry sand, water spray or alcohol-resistant foam to extinguish.

P403+P233-Store in a well-ventilated place. Keep container tightly closed.

P403+P235-Store in a well-ventilated place. Keep cool.

P405-Store locked up.

P501-Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent
61789-92-2	Gum Mastic	10 w/v
67-63-0	Isopropyl Alcohol	Balance

Section 4 - First Aid Measures

**Eye Exposure:** In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Seek medical attention.

**Dermal Exposure:** In case of skin contact, flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing and shoes. Seek medical attention.

**Oral Exposure:** If swallowed, seek immediate medical attention. Do not induce vomiting. Rinse mouth with water.

**Inhalation Exposure:** If inhaled, remove to fresh air. If breathing becomes difficult, call a physician.

Section 5 - Fire Fighting Measures

**General Information:** Containers can build up pressure if exposed to heat and/or fire. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Vapors can travel to a source of ignition and flash back. Will burn if involved in a fire. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures above the flashpoint. Use water spray to keep fire-exposed containers cool. Containers may explode in the heat of a fire.

**Extinguishing Media:** For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. For large fires, use water spray, fog, or alcohol-resistant foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do NOT use straight streams of water.

**Hazardous Combustion Products:** Carbon oxides, peroxides, irritating and toxic fumes and gases.

Flash Point: Not available Autoignition Temperature: Not available Explosion Limits, Lower: Not available Upper: Not available NFPA Rating: (estimated) Health: 2; Flammability: 3; Instability: 0

Section 6 - Accidental Release Measures

## **Procedure(s) of Personal Precaution(s):**

Wear personal protective equipment. Do not ingest or inhale. Do not get on skin or clothing. Do not get in eyes. Ensure adequate ventilation. Keep away from heat. Eliminate all sources of ignition. Take precautionary measures against static discharges.

**Methods for Cleaning up:** Absorb with sand, earth, or vermiculite. Carefully sweep up and containerize for proper disposal. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Do not release to the environment. Do not release to drains.

Section 7 - Handling and Storage

Use care when handling. Wear personal protective equipment. Wash thoroughly after handling. Use with adequate ventilation. Do not ingest or inhale. Do not get on skin or clothing. Do not get in eyes. Store in a tightly closed container in a **refrigerator**. Keep away from incompatible materials. Keep away from open flames, hot surfaces, and sources of ignition. Store away from direct sunlight (light sensitive). Use spark-proof tools and explosion-proof equipment. Properly ground metal parts of equipment. Take precautionary

measures against static discharges. Vapors heavier than air may travel considerable distance and ignite or explode.

Section 8 - Exposure Controls, Personal Protection

**Engineering Controls:** Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

## **Personal Protective Equipment**

**Eyes:** Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

**Skin:** Wear appropriate protective gloves to prevent skin exposure.

**Clothing:** Wear appropriate protective clothing to prevent skin exposure.

**Respirators:** A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

## **Exposure Limits:**

Chemical Name	ACGIH - TLV	NIOSH - IDLH	OSHA - Final PELs
Gum Mastic CAS#61789-92-2	Not listed	Not listed	Not listed
Isopropyl Alcohol CAS#67-63-0	200 ppm TWA 400 ppm STEL	400 ppm TWA 980 mg/m3 TWA 500 ppm STEL 1225 mg/m3 STEL 2000 ppm IDLH	400 ppm TWA 980 mg/m3 TWA

**OSHA Vacated PELS:** Isopropyl Alcohol: 400 ppm TWA; 980 mg/m3 TWA; 500 ppm STEL; 1225 mg/m3 STEL

Section 9 - Physical and Chemical Properties

Physical State: Liquid Appearance: Clear, colorless Odor: Alcohol-like Vapor Pressure: Not available Odor Threshold: Not available Vapor Density: Not available pH: Approx. 4.5-5.0 Relative Density: Not available Melting point/freezing point: Not available Solubility: Miscible with water Boiling Point: Not available Flash Point: Not available Evaporation Rate: Not available Flammability (solid, gas): Not available Partition coefficient: n-octanol/water: Not available Autoignition Temperature: Not available Decomposition Temperature: Not available Viscosity: Not available Specific Gravity/Density: Not available

Section 10 - Stability and Reactivity

**Chemical Stability:** Stable under normal temperatures and pressures.

**Conditions to Avoid:** Incompatible materials, ignition sources, excess heat, hot surfaces, open flames, and oxidizers. Direct sunlight.

**Incompatibilities with Other Materials:** Strong oxidizing agents, acids, halogens, halogenated compounds, acid anhydrides, and aluminum.

**Hazardous Decomposition Products:** Carbon oxides, peroxides, irritating and toxic fumes and gases.

Section 11 - Toxicological Information

#### CAS#61789-92-2 Gum Mastic:

LD50 Oral: Not available LD50 Dermal: >5000 mg/kg (rabbit) LC50 Inhalation: Not available

**Carcinogenicity:** Gum Mastic CAS#61789-92-2 is not listed by IARC, NTP, ACGIH, OSHA, or California Prop. 65.

#### CAS#67-63-0 Isopropyl Alcohol: RTECS#: NT8050000

LD50 Oral: 5045 mg/kg (rat) LD50 Oral: 3600 mg/kg (mouse) LD50 Dermal: 12800 mg/kg (rat) LD50 Inhalation: 72.6 mg/L 4h (rat)

**Carcinogenicity:** Isopropyl Alcohol CAS#67-63-0 is not listed by NTP, ACGIH, OSHA, or California Prop. 65. Isopropyl Alcohol is listed by IARC (Group 3, Unclassifiable as to Carcinogenicity in Humans).

**Information on the likely routes of exposure:** Routes of entry anticipated: oral, dermal, inhalation, and eye.

Epidemiology: Not available.
Teratogenicity: Not available.
Reproductive Effects: Not available.
Developmental Effects: Not available.
Neurotoxicity: Not available.
Mutagenicity: Not available.
Specific Target Organ Toxicity, Single Exposure: Respiratory system, and central nervous system.
Specific Target Organ Toxicity, Repeated Exposure: Kidney and liver.

**Symptoms associated with exposure:** May cause CNS depression. Causes serious eye irritation. Prolonged or repeated exposure can cause headache, dizziness, tiredness, nausea, and vomiting.

# The toxicological properties of this material have not been thoroughly investigated.

Section 12 - Ecological Information

**Ecotoxicity:** Do not release to the environment. Do not release to drains.

## CAS#67-63-0 Isopropyl Alcohol:

LC50, freshwater fish: 11130 mg/L 96h static (pimephales promelas)(fathead minnow) LC50, freshwater fish: >1400000 µg/L 96h (lepomis macrochirus)(bluegill) LC50, freshwater fish: 9640 mg/L 96h flow-through (pimephales promelas)(fathead minnow) EC50, freshwater algae: >1000 mg/L 72h (desmodesmus subspicatus)(green algae) EC50, freshwater algae: >1000 mg/L 96h (desmodesmus subspicatus)(green algae) EC50, water flea: 13299 mg/L 48h (daphnia magna) EC50, water flea: 9714 mg/L 24h EC50, microtox: 35390 mg/L 5min (photobacterium phosphoreum)

### Persistence and degradability: Not available.

**Bio-accumulative potential:** Not available.

**Mobility:** Will likely be mobile in the environment due to its volatility.

Section 13 - Disposal Considerations

**DISPOSAL:** Dispose of in accordance with all federal, state, and local regulations.

Section 14 – Transport Information

**DOT** Proper shipping name: Isopropyl Alcohol UN1219 PG II Hazard class 3 (flammable)

Section 15 - Regulatory Information

#### **Canada Regulatory Information**

WHMIS Classification: This product has been classified in accordance with the hazard criteria of the CPR, and the SDS contains all the information required by the CPR.

Section 16 - Additional Information

#### **SDS Creation Date:** 11/1/12 **Revision #1:** 2/23/15 RC **Revision #2:** 7-17-23

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Rowley Biochemical, Inc. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages, howsoever arising, even if Rowley Biochemical, Inc. has been advised of the possibility of such damages.